

Appendix A



Commport settings



Commport communication speed and protocol settings, can be set in the **Commport** section of the Configuration program.

Configuration program can be downloaded from our web-site's SUPPORT section.

LinTronic CONFIGURATOR , Version: 002.000.005, Revision: 006

CheckForUpdates BootLoader DataSampler SpyWare Log OnlineHelp PDF

TT455-RT-238
RELAY 108
RELAY 208
Configuration
Help (online)
LinTronic Online

Transmitted 0100055001001001014 Packages 6
Received 0001055001236 Packages 6
Type RELAY 208
Hardware 208
Software 001.034.037
Date_Time Nov 25 2010 13:26:11

RELAY 208

Products Address Computers Commport

AUTO

Baudrate
☐ 2400 ☐ 4800 ☐ 9600 ☒ 19200
☐ 38400 ☐ 57600 ☐ 76800 ☐ 115200

CommPort 15

Parity ☒ None ☐ Odd ☐ Even

Databits ☒ 8 ☐ 7

Stopbits ☒ 1 ☐ 2

Ports

ChangeBaudrate
Changes products baudrate.
RespondDelay
Changes respons delay. Only used when communicating over network.

Removing and re-inserting a USB cable might change the commport number. Insert cable into computer, wait 5-10 seconds, then click this button to see your systems commports.

Appendix B



Computer receives command



If you connect a LinTronic product to our Configuration program ... can be downloaded from our website's SUPPORT section ... then you will see any received command being shown in the RECEIVED text field.

NOTE: Start Of Telegram (SOT <) and End Of Telegram (EOT >) have both been stripped off.

LinTronic CONFIGURATOR , Version: 002.000.005, Revision: 006

CheckForUpdates BootLoader DataSampler SpyWare Log OnlineHelp PDF

TT455-RT-238
RELAY 108
RELAY 208
Configuration
Help (online)
LinTronic Online

Transmitted 0100055001001001014 Packages 6
Received 0001055001236 Packages 6
Type RELAY 208
Hardware 208
Software 001.034.037
Date_Time Nov 25 2010 13:26:11

RELAY 208

Products Address Computers Commport

AUTO

Baudrate
☐ 2400 ☐ 4800 ☐ 9600 ☒ 19200
☐ 38400 ☐ 57600 ☐ 76800 ☐ 115200

CommPort 15

Parity ☒ None ☐ Odd ☐ Even

Databits ☒ 8 ☐ 7

Stopbits ☒ 1 ☐ 2

Ports

ChangeBaudrate
Changes products baudrate.
RespondDelay
Changes respons delay. Only used when communicating over network.

Removing and re-inserting a USB cable might change the commport number. Insert cable into computer, wait 5-10 seconds, then click this button to see your systems commports.

Appendix C



Computer transmits command



If you connect a LinTronic product to our Configuration program ... can be downloaded from our website's SUPPORT section ... then you will see any transmitted command being shown in the TRANSMITTED text field.

NOTE: Start Of Telegram (SOT <) and End Of Telegram (EOT >) have both been stripped off.

